



Fireplaces for fireplaces

## Fireplace 840 Horizontal Shutter

The 840 Horizontal fireplace will follow the lines of your interior to blend in with stylish décor.

Reference: P928475



### Why this product?

#### - Fireplace decor

The range of decorative hearths is intended to be embedded in a formwork. Only the front door with original and clever decoration remains visible, offering a sober and design to the spectacle of the flames.

#### - Intermittent and prolonged combustion 3 hours

The device can operate alternately in intermittent or extended combustion mode. The intermittent mode requires frequent wood feeding. It is particularly powerful and respectful of the environment. The extended combustion mode, in reduced speed, makes it possible to obtain a duration of operation of 3 hours without intervention.

#### - Origin France Guarantee

The Origine France Garantie label is the only certification that certifies the French origin of the manufacture of a product. This labeling is validated by an independent body, in particular after an audit. (Bureau Veritas No. 7208672). OFG products are manufactured in France at the Invicta Group production sites.

#### - Post combustion system

Preheated air injection into the combustion chamber. The additional air intake from the rear helps destroy hydrocarbons at high temperatures. The combustion is complete and the pollution reduced.

#### - Clean glass

The clean glass system slows the clogging of the glazing. An air inlet on the top of the glass creates a protective veil. The preheated air is propelled along the glazing. It triggers the combustion of gases and volatile materials thus protecting the glass against smoke and soot deposition.

#### - Nozzle flap

The nozzle valve adjusts the draft of the appliance. His command is located above the door of the device. By opening the nozzle flap before opening the appliance door, you avoid flue gas discharge.

## Characteristics

POWER	12 kW
POWER MODULATION	8 to 18 kW
HEATING VOLUME	160 - 360 m <sup>3</sup>
HEATING SURFACE	65 - 145 m <sup>2</sup>
GREEN FLAME	7 stars
YIELD	77%
CO RATE	0.11%
CONCENTRATION DE POUSSIÈRES	24 mg/Nm <sup>3</sup>
INDICE DE PERFORMANCE	0.5
COMBUSTIBLE	Bûches de 33 cm
LONGUEUR DE BÛCHES MAXIMALE (HORIZONTALEMENT)	60 cm
CHARGEMENT	Façade
DÉPART DES FUMÉES	Dessus
DIAMÈTRE DE BUSE	200 mm
DIMENSIONS	H 703 x L 846 x P 465 mm
POIDS	125 kg
DESIGN	Traditionnel
CATÉGORIE DE LARGEUR (FOYERS, INSERTS)	840
MATIÈRE	Fonte
FINITION	Anthracite
NORME	EN 13229
GARANTIE	5 ans