



Fireplace inserts

Insert 800 Wide Angle Turbo

Take a seat in front of your fireplace, the show is grand thanks to the full glass of this large format model. A soft heat is diffused in the room.

Reference: P968843



Why this product?

- Hot air diffusion by forced ventilation

The unit is equipped with 2 axial 2-speed turbines with manual control via a switch. The turbines start automatically from 50 ° C.

- Intermittent and prolonged combustion 3 hours

The device can operate alternately in intermittent or extended combustion mode. The intermittent mode requires frequent wood feeding. It is particularly powerful and respectful of the environment. The extended combustion mode, in reduced speed, makes it possible to obtain a duration of operation of 3 hours without intervention.

- Optional sleeves

The cuffs for air distribution are available as an option. Reference P690080: kit 2 machetes + screws.

- Origin France Guarantee

The Origine France Garantie label is the only certification that certifies the French origin of the manufacture of a product. This labeling is validated by an independent body, in particular after an audit. (Bureau Veritas No. 7208672). OFG products are manufactured in France at the Invicta Group production sites.

- Post combustion system

Preheated air injection into the combustion chamber. The additional air intake from the rear helps destroy hydrocarbons at high temperatures. The combustion is complete and the pollution reduced.

- Wide Angle Outside Glass

Silk-screened glass positioned outside the door offering a modern style and a beautiful vision of the flames.

- Clean glass

The clean glass system slows the clogging of the glazing. An air inlet on the top of the glass creates a protective veil. The preheated air is propelled along the glazing. It triggers the combustion of gases and volatile materials thus protecting the glass against smoke and soot deposition.

Characteristics

POWER	12 kW
POWER MODULATION	8 to 18 kW
HEATING VOLUME	160 - 360 m ³
HEATING SURFACE	65 - 145 m ²
GREEN FLAME	7 stars
YIELD	75%
CO RATE	0.12%
DUST CONCENTRATION	40 mg / Nm ³
PERFORMANCE INDEX	0.7
COMBUSTIBLE	Logs of 33 cm
MAXIMUM LOG LENGTH (HORIZONTALLY)	64 cm
LOADING	Facade
DEPARTURE OF FUMES	Above
NOZZLE DIAMETER	200 mm
DIMENSIONS	H 636 x W 795 x D 470 mm
WEIGHT	161 kg
DESIGN	Contemporary
WIDTH CATEGORY (FIREPLACES, INSERTS)	800
MATERIAL	Cast Iron + Steel
FINISH	Anthracite
STANDARD	EN 13229
GUARANTEE	5 years
OPTIONS (ACCESSORIES)	Hot air outlet cuffs